



Notes:

1. Sign blank shall be 457mm (18") x variable length. If sign length is greater than 1,22m (48"), the sign must be stiffened with two 51mm (2") x 102 mm (4") Construction heart redwood stiffeners.
2. Sign blank shall be 2mm (0.080") gauge aluminum or 16 mm (5/8") ACV exterior grade plywood.
3. Sign shall be faced with 203mm (8") upper case letters and 152mm (6") lower case letters.
4. Sign sheeting shall be reflective engineer grade (Scotchlite) white copy and border on reflective engineer grade (Scotchlite) green background. Sheeting and copy shall be pressure sensitive.
5. City decal detail to be obtained from City.
6. Carriage bolt with 8 mm (5/16") galvanized hex head with flat washers, fiber washers, lockwasher and nut. Deform threads to prevent removal.

**Units are in metric
Non-metric units are in brackets**

ACAD FILENAME: MEDSIGN

CITY OF MENLO PARK STANDARD DETAILS



NO.	REVISIONS	DATE

**STREET NAME SIGN
MEDIAN ISLAND INSTALLATION**

APPROVED
Y. A. Qawa
Director of Engineering Services R.C.E. No. 40998

DRAWN CHECKED NN DATE 5-21-97 SCALE NTS SHEET 1

STD. DETAIL No.: **ST-11**